



Pro+100 | Pro+150

Smart, Sustainable Water Solutions for Life

From a morning shower to a freshly brewed cup of coffee, from swimming to eating fresh produce, water is in every facet of our lives.



- High flow professional grade control valve
- Intelligent digital management system
- Programmable self cleaning cycles for long life
- Superior filtration capacity for whole home treatment
- Easy plumbing connections with integral bypass valve
- Simple elegant lines and design



American Made
Components

CPK-PRO+100
CPK-PRO+150

Start enjoying the Kenai Pro+100 and Pro+150 difference today.

Contact a Kenai authorized dealer to install a Pro+ Professional Series Water Treatment System and start enjoying all the benefits of this whole home powerhouse.

Filtration

Removing contaminants from your water.

Water is the most important tool for our daily lifestyle. The quality and purity of the water in our homes is crucial to us and a critical component of a healthy diet. The responsibility of the 'final barrier' is on the homeowner to provide confidence in your water. This is entirely possible for your peace of mind with a properly applied water treatment system.

The water supplied to your home comes from one or a number of different sources depending on where you live. It can be from a lake, river, or groundwater from a well. The characteristics of the water will depend on the journey that it takes to get to your home. There will be particles, minerals, metals, and chemicals that are dissolved in the water.

In the typical home in the United States, we use approximately 60 gallons of water per person every day, on average.



Pro+100 | Pro+150

Systems with catalytic carbon remove chloramines, chlorine, pesticides, and most other VOC (Volatile Organic Chemicals). The Pro+100 and Pro+150 are designed to improve the quality of your water.

Catalytic Activated Carbon

- Higher capacity for chlorine reduction/removal
- Better reduction of THMs, VOCs and chloramines
- Reduction/removal of bad tastes and odors
- Better reduction of hydrogen sulfide
- More expensive



Pro+100

Pro+150

SPECIFICATIONS

Plumbing Connections

3/4", 1", or 1.25" NPT

3/4", 1", 1.25", or 1.5" PVC Glue

3/4", 1", 1.25", or 1.5" Sweat

3/4" or 1" Sharkbite

3/4" or 1" John Guest

Drain Connection

3/4" NPT

Service Flow Rates

12.7 gpm (ANSI/NSF Std 44 Equivalent)

Backwash/Rinse Flow

4.2 gpm

Operating Pressure

20 – 125 psi

Operating Water Temps

Min 40° F – Max 110° F

Electrical Supply

120 VAC 50/60 Hz



The Pro+100 and Pro+150 are also available with the Autotrol valve. Ask us for details

